

Page : 1 / 10

Revised edition no : 3 - 00

Date : 9 / 12 / 2015

Supersedes : 22 / 4 / 2013

Frisin ®

227009

SECTION 1. Identification of the substance/mixture and of the company/undertaking

 Trade name
 : Frisin ®

 SDS no
 : 227009

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

For fumigation.

Contact supplier for more uses information.

1.3. Details of the supplier of the safety data sheet

Company identification : AIR LIQUIDE Deutschland GmbH

Hans-Günther-Sohl-Straße 5 D-40235 Düsseldorf GERMANY

Telefon: +49 (0)211 6699-0 - Fax: +49 (0)211 6699-222

E-Mail address (competent person) : Info.SDB@AirLiquide.de

1.4. Emergency telephone number

Emergency telephone number : +49 (0)2151 398668

- Availability : (24 / 7)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

• Health hazards : Acute toxicity, Inhalation - Category 3 - Danger - (CLP : Acute Tox. 3) - H331

Skin irritation - Category 2 - Warning - (CLP: Skin Irrit. 2) - H315 Eye irritation - Category 2 - Warning - (CLP: Eye Irrit. 2) - H319

Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation - Category 3 -

Warning - (CLP : STOT SE 3) - H335

• Physical hazards : Gases under pressure - Compressed gas - Warning - (CLP: Press. Gas) - H280

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms





• Hazard pictograms code : GHS06 - GHS04

• Signal words : Danger

• Hazard statements : H280 - Contains gas under pressure; may explode if heated.

H331 - Toxic if inhaled.

H319 - Causes serious eye irritation. H315 - Causes skin irritation. H335 - May cause respiratory irritation.

· Precautionary statements

- Prevention : P260 - Do not breathe gas, vapours.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

- Response : P304+P340+P315 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Get immediate medical advice / attention.

P305+P351+P338+P315 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

In case of emergency: +49 (0)2151 398668

advice / attention.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P332+P313 - If skin irritation occurs: Get medical advice/attention.



Page: 2/10 Revised edition no: 3 - 00 Date: 9 / 12 / 2015

Supersedes: 22 / 4 / 2013

Frisin ®

227009

SECTION 2. Hazards identification (continued)

: P403 - Store in a well-ventilated place. - Storage

P405 - Store locked up.

2.3. Other hazards

Other hazards · None

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Mixture.

Substance name		Content [Vol-%]	CAS No EC No Index No Registration no.	Classification(DSD)	Classification(CLP)
Phosphine	:	1.7 %	7803-51-2 232-260-8 015-181-00-1 *2		Acute Tox. 1 (H330) Flam. Gas 1 (H220) Skin Corr. 18 (H314) Liq. Gas (H280) Aquatic Acute 1 (H400)
Nitrogen	:	98.3 %	7727-37-9 231-783-9		Press. Gas (H280)
			 *1		

Contains no other components or impurities which will influence the classification of the product.

- 1: Listed in Annex IV / V REACH, exempted from registration.
- * 2: Registration deadline not expired.
- * 3: Registration not required: Substance manufactured or imported < 1t/y

Full text of R-phrases see chapter 16. Full text of H-statements see chapter 16

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

In case of emergency: +49 (0)2151 398668

- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Irritation to the respiratory tract.

May cause irritation to skin.

May cause irritation to cornea (with temporary disturbance to vision).

Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: Obtain medical assistance.



Page : 3 / 10

Revised edition no : 3 - 00

Date : 9 / 12 / 2015

Supersedes: 22 / 4 / 2013

Frisin ®

227009

SECTION 5. Fire-fighting measures

5.1. Extinguishing media

Extinguishing media : All known extinguishants can be used.

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : Phosphorus oxides/acids.

5.3. Advice for firefighters

Specific methods : Move containers away from the fire area if this can be done without risk.

If possible, stop flow of product.

Use fire control measures appropriate to the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems.

Use water spray or fog to knock down fire fumes if possible.

Special protective equipment for fire

fighters

Use self-contained breathing apparatus.

Use chemically protective clothing.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for

firefighters.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Act in accordance with local emergency plan.

Stay upwind

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

In case of emergency: +49 (0)2151 398668

be safe.

Ensure adequate air ventilation.

Evacuate area. Try to stop release.

Use chemically protective clothing.

Monitor concentration of released product.

6.2. Environmental precautions

: Try to stop release.

Reduce vapour with fog or fine water spray.

6.3. Methods and material for containment and cleaning up

: Wash contaminated equipment or sites of leaks with copious quantities of water.

Hose down area with water.

Ventilate area.

6.4. Reference to other sections

Reference to other sections : See also sections 8 and 13.



Page: 4 / 10

Revised edition no: 3 - 00

Date: 9 / 12 / 2015

Supersedes : 22 / 4 / 2013

227009

Frisin ®

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Do not breathe gas.

Avoid release of product into atmosphere.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt. Avoid exposure, obtain special instructions before use.

Do not smoke while handling product.

Only experienced and properly instructed persons should handle gases under pressure. Ensure the complete gas system was (or is regularily) checked for leaks before use. Installation of a cross purge assembly between the cylinder and the regulator is

recommended.

Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when

system is placed out of service.

The product must be handled in accordance with good industrial hygiene and safety

procedures.

Consider pressure relief device(s) in gas installations.

Safe handling of the gas receptacle

Secure gas cylinder against overturning.

Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is

disconnected from equipment.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

Do not remove or deface labels provided by the supplier for the identification of the cylinder

contents.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.)

designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall

or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact

supplier.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to repair or modify container valves or safety relief devices.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Damaged valves should be reported immediately to the supplier.

7.2. Conditions for safe storage, including any incompatibilities

: Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Stored containers should be periodically checked for general condition and leakage. Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Containers should be stored in the vertical position and properly secured to prevent toppling.

Containers should be stored in the vertical position and properly secured to prevent toppling Container valve guards or caps should be in place.

In case of emergency: +49 (0)2151 398668

Keep away from combustible materials.

7.3. Specific end use(s)

: None.



Page: 5 / 10

Revised edition no: 3 - 00 Date: 9 / 12 / 2015

Supersedes: 22 / 4 / 2013

Frisin ®

227009

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Phosphine : ILV (EU) - 8 H - [mg/m3]: 0.14

> : ILV (EU) - 8 H - [ppm] : 0.1 : ILV (EU) - 15 min - [mg/m³] : 0.28 : ILV (EU) - 15 min - [ppm] : 0.2

: AGW (8h) - Germany [mg/m3] TRGS 900 : 0.14 : AGW (8h) - Germany [ppm] TRGS 900 : 0.1 : Exceeding factor AGW - Germany TRGS 900 : 2

DNEL: Derived no effect level (

Workers)

: Inhalation-short term (systemic) [mg/m3] : 0.28 **Phosphine**

: Inhalation-long term (systemic) [mg/m3]: 0.14

PNEC: Predicted no effect

concentration

: No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering

controls

: Provide adequate general and local exhaust ventilation.

Alarm detectors should be used when toxic gases may be released. Systems under pressure shoud be regularily checked for leakages.

Product to be handled in a closed system and under strictly controlled conditions.

Ensure exposure is below occupational exposure limits (where available).

Consider work permit system e.g. for maintenance activities.

Preferably use only permanent leak-tight installations (e.g. welded pipes).

8.2.2. Individual protection measures, :

e.g. personal protective equipment

Keep self contained breathing apparatus readily available for emergency use.

Keep suitable chemically resistant protective clothing readily available for emergency use.

Wear leather safety gloves and safety shoes when handling cylinders.

Wear safety glasses with side shields

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered.

PPE compliant to the recommended EN/ISO standards should be selected.

· Eye/face protection Wear safety glasses with side shields

Standard EN 166 - Personal eye-protection.

Skin protection

- Hand protection Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk.

- Other Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

 Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

 Thermal hazards : None necessary.

8.2.3. Environmental exposure

controls

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

In case of emergency: +49 (0)2151 398668

specific methods for waste gas treatment.



Page: 6 / 10

Revised edition no: 3 - 00 Date: 9 / 12 / 2015

Supersedes: 22 / 4 / 2013

Frisin ®

227009

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas. Colour Colourless

Odour : Rotten fish. Garlic like.

Mixture contains one or more component(s) which have the following odour(s):

There may be no odour warning properties, odour is subjective and inadequate to warn of

overexposure

Odour threshold : Odour threshold is subjective and inadequate to warn for overexposure.

pH value : Not applicable for gas-mixtures.

Molar mass [q/mol] : Not applicable for gases and gas-mixtures.

Melting point [°C] : Not applicable for gas-mixtures. : Not applicable for gas-mixtures. Boiling point [°C] Flash point [°C] : Not applicable for gas-mixtures. Evaporation rate (ether=1) Not applicable for gas-mixtures. Flammability range [vol% in air] : Not applicable for gas-mixtures.

: Not applicable. Vapour pressure [20°C] Relative density, gas (air=1) : Lighter or similar to air.

Solubility in water [mg/l] : • Nitrogen : 20 • Phosphine : 300

Solubility in water of component(s) of the mixture :

Partition coefficient n-octanol/water [: Not applicable for gas-mixtures.

log Pow]

Viscosity at 20°C [mPa.s] : Not applicable. **Explosive Properties** : Not applicable.

Oxidising properties : None.

9.2. Other information

Other data : None.

SECTION 10. Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

: Can ignite spontaneously in air (fire cannot be put out). Can form spontaneous, violently

explosive mixture in air.

10.4. Conditions to avoid

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

: Air, Oxidiser.

For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

In case of emergency: +49 (0)2151 398668



Page: 7 / 10

Revised edition no: 3 - 00

Date: 9 / 12 / 2015

Supersedes : 22 / 4 / 2013

Frisin ®

227009

In case of emergency: +49 (0)2151 398668

SECTION 10. Stability and reactivity (continued)

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Toxic if inhaled.

Rat inhalation LC50 [ppm/4h] : • Phosphine : 10

Skin corrosion/irritation : Irritation to skin .

Serious eye damage/irritation : Irritation to eyes.

Respiratory or skin sensitisation

Carcinogenicity

Serm cell mutagenicity

Toxic for reproduction: Fertility

Toxic for reproduction: unborn child

STOT-single exposure

STOT-repeated exposure

Aspiration hazard

No known effects from this product.

Irritation to the respiratory tract.

No known effects from this product.

SECTION 12. Ecological information

12.1. Toxicity

Assessment

Classification criteria are not met.

12.2. Persistence and degradability

Assessment : No data available.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : No data available.

12.5. Results of PBT and vPvB assessment

: No data available.

12.6. Other adverse effects

: May cause pH changes in aqueous ecological systems.

Effect on ozone layer : None.

Effect on the global warming : No known ecological damage caused by this product.



Page: 8 / 10
Revised edition no: 3 - 00

Date: 9 / 12 / 2015

Supersedes : 22 / 4 / 2013

Frisin ®

227009

In case of emergency: +49 (0)2151 398668

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Must not be discharged to atmosphere.
Contact supplier if quidance is required.

Refer to the code of practice of EIGA (Doc. 30/10 "Disposal of Gases, downloadable at http://www.eiga.org) for more guidance on suitable disposal methods

Ensure that the emission levels from local regulations or operating permits are not exceeded.

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 04 - gases in pressure containers (including halons) containing dangerous substances.

13.2. Additional information

: None.

SECTION 14. Transport information

14.1. UN number

UN number : 1955

Labelling ADR, IMDG, IATA



: 2.3 : Toxic gas.

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : COMPRESSED GAS, TOXIC, N.O.S. (Phosphine, Nitrogen)
Transport by air (ICAO-TI / IATA-DGR) : COMPRESSED GAS, TOXIC, N.O.S. (Phosphine, Nitrogen)
Transport by sea (IMDG) : COMPRESSED GAS, TOXIC, N.O.S. (Phosphine, Nitrogen)

14.3. Transport hazard class(es)

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 1 T
H.I. nr : 26

Tunnel Restriction : C/D : Passage forbidden through tunnels of category C when carried in tanks. Passage

forbidden through tunnels of category D and E.

Transport by air (ICAO-TI / IATA-DGR)

Transport by sea (IMDG)

 $\begin{array}{lll} \textbf{Emergency Schedule (EmS) - Fire} & : & F-C \\ \textbf{Emergency Schedule (EmS) - Spillage} & : & S-U \\ \end{array}$

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable.

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : No



Page: 9 / 10 Revised edition no: 3 - 00

Date: 9 / 12 / 2015

Supersedes: 22 / 4 / 2013

Frisin ®

227009

SECTION 14. Transport information (continued)

14.6 Special precautions for user

Packing Instruction(s) : P200 Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft

Transport by sea (IMDG)

: DO NOT LOAD IN PASSENGER AIRCRAFT.

Cargo Aircraft only : FORBIDDEN.

Special precautions for user : - Ensure there is adequate ventilation.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency. Before transporting product containers: - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk according to Annex : Not applicable. II of MARPOL 73/78 and the IBC Code

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Seveso directive 96/82/EC : Covered

National legislation

: Ensure all national/local regulations are observed.

: [German regulations]

BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 "Ortsbewegliche Druckgasbehälter", TRGS 2141, BGRegel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit

In case of emergency: +49 (0)2151 398668

Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900.

- 4. BlmschV (Germany)

- Water hazard class (WGK) : WGK Germany: 1 - Low hazard to waters.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.



Page: 10 / 10

Revised edition no: 3 - 00

Date: 9 / 12 / 2015

Supersedes: 22 / 4 / 2013

Frisin ®

227009

SECTION 16. Other information

Indication of changes

: Revised safety data sheet in accordance with commisssion regulation (EU) No 453/2010

Training advice

: Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

Receptacle under pressure.

Further information

This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP.

List of full text of H-statements in section 3.

H220 - Extremely flammable gas.

H280 - Contains gas under pressure; may explode if heated.

H314 - Causes severe skin burns and eye damage.

H330 - Fatal if inhaled.

H400 - Very toxic to aquatic life.

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility

and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or

damage resulting from its use can be accepted.

End of document

In case of emergency: +49 (0)2151 398668